### CMSC 28100

# Introduction to Complexity Theory

Autumn 2025

Instructor: William Hoza



# Modified Post's Correspondence Problem

- Given: A list of "dominos"  $\begin{bmatrix} t_1 \\ b_1 \end{bmatrix}$ ,  $\begin{bmatrix} t_2 \\ b_2 \end{bmatrix}$ ,  $\begin{bmatrix} t_3 \\ b_3 \end{bmatrix}$ , ...,  $\begin{bmatrix} t_k \\ b_k \end{bmatrix}$
- Goal: Determine whether it is possible to construct a "match"
- A "match" is a sequence of dominos  $\begin{vmatrix} t_1 \\ b_1 \end{vmatrix} \begin{vmatrix} t_{i_1} \\ b_{i_2} \end{vmatrix} \begin{vmatrix} t_{i_2} \\ b_{i_3} \end{vmatrix} \begin{vmatrix} t_{i_3} \\ b_{i_4} \end{vmatrix} \begin{vmatrix} t_{i_5} \\ b_{i_5} \end{vmatrix} \cdots$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} \begin{bmatrix} t_{i_1} & t_{i_2} & t_{i_3} & t_{i_4} & t_{i_5} \\ b_{i_1} & b_{i_2} & b_{i_3} & b_{i_4} & b_{i_5} \end{bmatrix} \dots \begin{bmatrix} t_{i_n} \\ b_{i_n} \end{bmatrix}$$

such that 
$$t_1 t_{i_1} t_{i_2} \cdots t_{i_n} = b_1 b_{i_1} b_{i_2} \cdots b_{i_n}$$

Using the same domino multiple times is permitted

Lemma: MPCP is undecidable

### Proof that MPCP is undecidable



- Assume there is a TM P that decides MPCP
- Let's construct a new TM H that decides HALT

#### Given $\langle M, w \rangle$ :

- 1. Construct dominos  $t_1, \dots, t_k, b_1, \dots b_k$  based on M and w (details on next slide)
- 2. Simulate P on  $\langle t_1, ..., t_k, b_1, ..., b_k \rangle$
- 3. If *P* accepts, accept. If *P* rejects, reject.

H

# The dominos for $\langle M, w \rangle$

• 
$$(q_0 \sqcup w)$$
 ,  $((q_{accept}))$  ,  $(q_{accept})$  , and  $(q_{reject})$ 

- For every  $q \in Q \setminus \{q_{\mathrm{accept}}, q_{\mathrm{reject}}\}$  and every  $b \in \Sigma$ :
  - If  $\delta(q,b)=(q',b',\mathrm{R})$ , we include  $\begin{vmatrix}qb)\\b'q'\,\sqcup\rangle$ , and we include  $\begin{vmatrix}qba\\b'q'a\end{vmatrix}$  for every  $a\in\Sigma$
  - If  $\delta(q,b)=(q',b',\mathrm{L})$ , we include  $\begin{vmatrix} qb \\ (q'\sqcup b' \end{vmatrix}$ , and we include  $\begin{vmatrix} aqb \\ q'ab' \end{vmatrix}$  for every  $a\in\Sigma$
- $b \atop b$  ,  $bq_{\rm accept} \atop q_{\rm accept}$  ,  $q_{\rm accept}b \atop q_{\rm accept}$  ,  $q_{\rm reject}b \atop q_{\rm reject}$  , and  $bq_{\rm reject} \atop q_{\rm reject}$  for every  $b \in \Sigma$

### Proof that MPCP is undecidable

- Assume there is a TM P that decides MPCP
- Let's construct a new TM H that decides HALT



#### Given $\langle M, w \rangle$ :

- 1. Construct dominos  $t_1, ..., t_k, b_1, ... b_k$  based on M and w (details on preceding slides)
- 2. Simulate P on  $\langle t_1, ..., t_k, b_1, ..., b_k \rangle$
- 3. If *P* accepts, accept. If *P* rejects, reject.

#### Need to show:

- If *M* halts on *w*, then there is a match
- If there is a match,
   then M halts on w

### Domino Feature 1

• **Domino Feature 1:** For every non-halting configuration C of M, there is a sequence of dominos such that the top string is (C) and bottom string is (NEXT(C))


• Proof omitted, but here's an example:

• Think of this sequence as one "super-domino"

# If M halts on w, then there is a match

• Let  $C_0, \ldots, C_T$  be the halting computation history of M on w

Match:



•  $|D_i + 1| = |D_i| - 1$ 

### Proof that MPCP is undecidable

- Assume there is a TM P that decides MPCP
- Let's construct a new TM H that decides HALT



#### Given $\langle M, w \rangle$ :

- 1. Construct dominos  $t_1, ..., t_k, b_1, ... b_k$  based on M and w (details on preceding slides)
- 2. Simulate P on  $\langle t_1, ..., t_k, b_1, ..., b_k \rangle$
- 3. If *P* accepts, accept. If *P* rejects, reject.

#### Need to show:

- If M halts on w, then
   there is a match
- If there is a match,
   then M halts on w

### Domino Feature 3

• **Domino Feature 3:** If C is a non-halting configuration, then every

sequence of dominos in which the top string starts with (C) must begin


with the following super-domino:

$$(C)$$
  $(NEXT(C))$ 

Proof omitted

# If there is a match, then M halts on w

- Assume there is a match
- By Domino Feature 3, it must have the form



where  $C_T$  is a halting configuration and  $x \in \Gamma^*$ 

### Proof that MPCP is undecidable

- Assume there is a TM P that decides MPCP
- Let's construct a new TM H that decides HALT



#### Given $\langle M, w \rangle$ :

- 1. Construct dominos  $t_1, ..., t_k, b_1, ... b_k$  based on M and w (details on preceding slides)
- 2. Simulate P on  $\langle t_1, ..., t_k, b_1, ..., b_k \rangle$
- 3. If *P* accepts, accept. If *P* rejects, reject.

#### Need to show:

- If M halts on w, then
   there is a match
- If there is a match,
   then M halts on w

# Post's Correspondence Problem is undecidable

Post's correspondence problem, formulated as a language:

$$PCP = \{ \langle t_1, ..., t_k, b_1, ..., b_k \rangle : \exists i_1, ..., i_n \text{ such that } t_{i_1} \cdots t_{i_n} = b_{i_1} \cdots b_{i_n} \}$$


Theorem: PCP is undecidable

- Proof outline:
  - Step 1: Reduce HALT to a modified version ("MPCP")
  - Step 2: Reduce MPCP to PCP

### Proof that PCP is undecidable



- Assume there is a TM P that decides PCP
- Let's construct a new TM M that decides MPCP
- For a string  $u=u_1u_2\dots u_n$ , define  $\overline{u}=u_1\star u_2\star \dots \star u_n$



Given  $\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} \begin{bmatrix} t_2 \\ b_2 \end{bmatrix} \begin{bmatrix} t_3 \\ b_3 \end{bmatrix} \dots \begin{bmatrix} t_k \\ b_k \end{bmatrix}$ :

1. Simulate P on  $\begin{bmatrix} \star \overline{t_1} \\ \star \overline{b_1} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_1} \\ \overline{b_1} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_2} \\ \overline{b_2} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_3} \\ \overline{b_3} \star \end{bmatrix} \dots \begin{bmatrix} \star \overline{t_k} \\ \overline{b_k} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_k} \\ \overline{b_k} \star \end{bmatrix}$ 

2. If *P* accepts, accept. If *P* rejects, reject.

• Suppose the MPCP instance has a match:

• Then the PCP instance also has a match:

Given  $\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} \begin{bmatrix} t_2 \\ b_2 \end{bmatrix} \begin{bmatrix} t_3 \\ b_3 \end{bmatrix} \dots \begin{bmatrix} t_k \\ b_k \end{bmatrix}$ :

1. Simulate P on  $\begin{bmatrix} \star \overline{t_1} \\ \star \overline{b_1} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_2} \\ \overline{b_2} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_3} \\ \overline{b_3} \star \end{bmatrix} \dots \begin{bmatrix} \star \overline{t_k} \\ \overline{b_k} \star \end{bmatrix} \begin{bmatrix} \star \overline{t_k} \\ \overline{b_k} \star \end{bmatrix}$ 2. If P accepts, accept. If P rejects, reject.

- Conversely, suppose the PCP instance has a match
- Must start with  $\left|\begin{smallmatrix}\star \overline{t_1}\\\star \overline{b_1}\star\end{smallmatrix}\right|$ , because that's the only domino in which the top string and bottom string start with the same symbol
- Delete all \* symbols ⇒ MPCP match

# Post's Correspondence Problem is undecidable

Post's correspondence problem, formulated as a language:

$$PCP = \{ \langle t_1, ..., t_k, b_1, ..., b_k \rangle : \exists i_1, ..., i_n \text{ such that } t_{i_1} \cdots t_{i_n} = b_{i_1} \cdots b_{i_n} \}$$

Theorem: PCP is undecidable


- Proof outline:
  - Step 1: Reduce REJECT to a modified version ("MPCP")
  - Step 2: Reduce MPCP to PCP

# Post's Correspondence Problem: Recap

- Post's Correspondence Problem seems like "just a domino puzzle"
- However, we showed how to build a computer out of dominos!
- PCP was secretly a problem about Turing machines all along!

# Undecidability

- Known undecidable languages:
  - SELF-REJECTORS
  - HALT
  - PCP and MPCP
- Next: One more example



# The acceptance problem

- Informal problem statement: Given a Turing machine M and an input w, determine whether M accepts w.
- The same problem, formulated as a language:


 $ACCEPT = {\langle M, w \rangle : M \text{ is a Turing machine that accepts } w}$ 

HALT and ACCEPT are both about predicting TMs' behavior

Theorem: ACCEPT is undecidable

### Code as data II

- Our proof that ACCEPT is undecidable will involve Turing machines
   constructing Turing machines
- Turing machines can both read and write descriptions  $\langle M \rangle$  where M is a Turing machine



"Drawing Hands." (1948 lithograph by M. C. Escher)

### Proof that ACCEPT is undecidable

- Assume there is a TM A that decides ACCEPT
- Let's construct a new TM H that decides HALT

# Given $\langle M, w \rangle$ :

1. Construct  $\langle M' \rangle$ , where M' is the following TM:

#### Given x:

- 1. Simulate M on x
- If M halts, accept.
- Simulate A on  $\langle M', w \rangle$
- If A accepts, accept. If A rejects, reject.

If M halts on w...

- Then M' accepts w
- Therefore, A accepts  $\langle M', w \rangle$
- Therefore, H accepts  $\langle M, w \rangle$

If M loops on w...

- Then M' loops on w
- Therefore, A rejects  $\langle M', w \rangle$



### Some more undecidable problems

- We have seen several interesting examples of undecidable languages
  - SELF-REJECTORS, HALT, PCP, MPCP, ACCEPT
- I'll describe a few more examples one more example
- Each can be proven undecidable via reduction from HALT
- But we will not do the proofs
- (This material will not be on exercises or exams)

# Hilbert's 10<sup>th</sup> problem

 Informal problem statement: Given a polynomial equation with integer coefficients such as

$$x^2 + 3xz + y^3 + z^2x^2 = 4xy^2 + 6yz + 2$$
,

determine whether there is an integer solution

• As a language: HILBERT10 =  $\{\langle p, q \rangle : \exists \vec{x} \text{ such that } p(\vec{x}) = q(\vec{x})\}$ 

Theorem: HILBERT10 is undecidable