### CMSC 28100

# Introduction to Complexity Theory

Autumn 2025

Instructor: William Hoza




### Midterm exam

- Midterm exam will be in class on Friday, October 24
- To prepare for the midterm, you only need to study the material prior to this point
- The midterm will be about Turing machines, decidability, and undecidability

# Which problems can be solved through computation?


### Applying our theory

- **Question:** In the year 1988, were there 50 U.S. senators, every pair of which voted the same way more than 50% of the time?
- Step 1: Gather data



### Agreement graph

- Step 2: Construct "agreement graph"
- Edge  $\{u,v\}$  means that senators u and v agreed on most votes
- **Question:** Are there 50 vertices in this graph that are all adjacent to one another?



• A k-clique in a graph G = (V, E) is a set  $S \subseteq V$  such that |S| = k and every two vertices in S are connected by an edge

• Example: This graph has a 4-clique

### Which of the following statements is **false**?


A: Every vertex in a k-clique has degree at least k-1

C: If G has fewer than  $\binom{k}{2}$  edges, then G does not have a k-clique

**B:** A single graph might have many *k*-cliques

D: If every vertex has degree at least k-1, then G has a k-clique


Respond at PollEv.com/whoza or text "whoza" to 22333



- Let CLIQUE =  $\{\langle G, k \rangle : G \text{ has a } k\text{-clique}\}$
- Example: Let G be the graph with the following adjacency matrix
- Does *G* have a 4-clique?

	а	b	С	d	е	f	g
a	0	1	1	0	0	1	0
b	1	0	0	1	1	0	1
С	1	0	0	0	1	0	1
d	0	1	0	0	1	0	1
e	0	1	1	1	0	1	1
f	1	0	0	0	1	0	1
g	0	1	1	1	1	1	0

- Let CLIQUE =  $\{\langle G, k \rangle : G \text{ has a } k\text{-clique}\}$
- Example: Let G be the graph with the following adjacency matrix



	а	b	С	d	е	f	g
а	0	1	1	0	0	1	0
b	1	0	0	1	1	0	1
С	1	0	0	0	1	0	1
d	0	1	0	0	1	0	1
е	0	1	1	1	0	1	1
f	1	0	0	0	1	0	1
g	0	1	1	1	1	1	0

- Let CLIQUE =  $\{\langle G, k \rangle : G \text{ has a } k\text{-clique}\}$
- Claim: CLIQUE is decidable
- **Proof sketch:** Given  $\langle G, k \rangle$  where G = (V, E), try all possible subsets  $S \subseteq V$ 
  - Check whether |S| = k
  - Check whether  $\{u, v\} \in E$  for every  $u, v \in S$  such that  $u \neq v$
- If we find a k-clique, accept; otherwise, reject.

- Question: In the year 1988, were there 50 U.S. senators, every pair of which voted the same way more than 50% of the time?
- Step 1: Gather data 🗸
- Step 2: Construct agreement graph 🗸
- Step 3: Apply CLIQUE algorithm

# Our algorithm is so slow that it's worthless



- Question: In the year 1988, were there 50 U.S. senators, every pair of which voted the same way more than 50% of the time?
- Checking all possible sets of senators would take longer than a lifetime!
- One begins to feel that CLIQUE might as well be undecidable!

Which problems

can be solved

through computation?

### Refining our model



- Our model so far: Decidable vs. undecidable
- Now we will refine our model
  - We only have a limited amount of time (and other resources)
- "Complexity theory" vs. "Computability theory"

### Time complexity



- Let *M* be a Turing machine
- The time complexity of M is a function  $T_M: \mathbb{N} \to \mathbb{N}$

$$T_M(n) := \max_{w \in \{0,1\}^n} (\text{running time of } M \text{ on } w)$$

• We focus on the worst-case *n*-bit input

### Scaling behavior

- We focus on the limiting behavior of  $T_M(n)$  as  $n \to \infty$
- How "quickly" does the running time increase when we consider larger and larger inputs?

### Asymptotic analysis

• Two possible time complexities:

$$T_1(n) = 3n^2 + 14$$
  
 $T_2(n) = 2n^2 + 64n + \lceil \sqrt{n} \rceil$ 

- When n is large, the leading  $C \cdot n^2$  term dominates
- We will ignore the low-order terms and the leading coefficient C
- We focus on the  $n^2$  part ("quadratic time")


### Big-O notation

- Let  $T, f: \mathbb{N} \to [0, \infty)$  be any two functions
- **Definition:** We say that T is O(f) if there exist  $C, n_* \in \mathbb{N}$  such that for every  $n > n_*$ , we have  $T(n) \leq C \cdot f(n)$
- Notation:  $T \in O(f)$  or  $T \leq O(f)$  or T = O(f)

### Big-O notation examples

- $3n^2 + 14$  is  $O(n^2)$
- $3n^2 + 14$  is  $O(n^2 + n)$
- $3n^2 + 14$  is  $O(n^3)$
- $3n^2 + 14$  is not  $O(n^{1.9})$

### Example: Palindromes



Claim: There exists a Turing machine that decides

PALINDROMES with time complexity  $O(n^2)$ .

- Proof sketch: Recall our Turing machine that decides PALINDROMES
- At most n/2 back-and-forth passes over the input
- Each back-and-forth pass takes O(n) steps
- Total time complexity:  $O(n) \cdot n/2 = O(n^2)$

### Optimality

Is there a faster Turing machine that decides PALINDROMES?

• Answer: No

• Use  $big-\Omega$  notation to make this precise

### $\mathsf{Big} extsf{-}\Omega$

- Let  $T, f: \mathbb{N} \to [0, \infty)$  be any two functions
- We say that T is  $\Omega(f)$  if there exist  $c \in (0,1)$  and  $n_* \in \mathbb{N}$  such that for every  $n > n_*$ , we have  $T(n) \geq c \cdot f(n)$
- Example:  $0.1n^2+14$  is  $\Omega(n^2)$  and  $\Omega(n)$ , but not  $\Omega(n^3)$

### Palindromes time complexity lower bound

Let M be a one-tape Turing machine

**Theorem:** If *M* decides PALINDROMES, then

the time complexity of M is  $\Omega(n^2)$ .

(Proof omitted)

### Palindromes, revisited

**Claim:** There exists a two-tape Turing machine M that decides PALINDROMES with time complexity O(n).

### Proof sketch:

- 1. Copy the input to tape 2
- 2. Scan tape 1 from left to right and scan tape 2 from right to left to compare

### Multi-tape Turing machines, revisited

- Multi-tape TMs can decide PALINDROMES in O(n) time...
- But single-tape TMs require  $\Omega(n^2)$  time!
- So multi-tape / single-tape TMs are not equivalent after all?

### Exponential vs. polynomial

- In this course, we are not concerned with the distinction between O(n) time and  $O(n^2)$  time
  - We're happy with either
- Our focus: The distinction between a polynomial time complexity, such as  $T(n)=n^2$ , and an exponential time complexity, such as  $T(n)=2^n$ 
  - Usable vs. useless

### Exponential vs. polynomial

- We write T(n) = poly(n) if there is some k such that  $T(n) = O(n^k)$
- Exponentials grow much faster than polynomials!
- We can make this precise using little-o and little- $\omega$  notation

### Little-o notation

- Let  $T, f: \mathbb{N} \to [0, \infty)$  be any two functions
- We say that T is o(f) if for every  $c \in (0,1)$ , there exists  $n_* \in \mathbb{N}$  such that for every  $n > n_*$ , we have  $T(n) < c \cdot f(n)$
- Equivalent:

$$\lim_{n \to \infty} \frac{T(n)}{f(n)} = 0$$

### Little- $\omega$ notation

- Let  $T, f: \mathbb{N} \to [0, \infty)$  be any two functions
- We say that T is  $\omega(f)$  if for every  $C \in \mathbb{N}$ , there exists  $n_* \in \mathbb{N}$  such that for every  $n > n_*$ , we have  $T(n) > C \cdot f(n)$
- Equivalent:

$$\lim_{n \to \infty} \frac{T(n)}{f(n)} = \infty$$

### Exponential vs. polynomial

**Claim:** For every constant  $k \in \mathbb{N}$ , we have  $n^k = o(2^n)$ 

• **Proof:** If  $n \ge k + 1$ , then

$$2^{n} = \text{\# subsets of } \{1, 2, \dots, n\} = \sum_{i=0}^{n} {n \choose i} \ge {n \choose k+1} \ge \left(\frac{n}{k+1}\right)^{k+1}$$
$$= \Omega(n^{k+1})$$
$$= \omega(n^{k}).$$