

CMSC 28100

Introduction to Complexity Theory

Autumn 2025

Instructor: William Hoza



~~Which problems
can be solved
through computation?~~


Complexity theory:

The study of computational resources

Computational resources: Fuel for algorithms



TIME




SPACE



RANDOMNESS



ADVICE



QUANTUM PHYSICS



COMMUNICATION

P vs. NP vs. PSPACE vs. EXP


- $P \subseteq NP \subseteq PSPACE \subseteq EXP$
- What we expect: All of these containments are **strict**
- What we can prove: **At least one** of these containments is strict. (Why?)

Sublinear-space computation


- Can we solve any interesting problems using $o(n)$ space?
- The one-tape Turing machine is the **not the right model** of computation for studying sublinear-space algorithms

Sublinear-space computation

Read-only input tape →



Read-write work tape →




The complexity class $\text{SPACE}(S)$

- Let $Y \subseteq \{0, 1\}^*$ and let $S: \mathbb{N} \rightarrow \mathbb{N}$ be a function (space bound)
- **Definition:** $Y \in \text{SPACE}(S)$ if there is a two-tape Turing machine M such that:
 - M decides Y
 - M never modifies the symbols written on tape 1
 - Tape 1 head is always located within one cell of the input
 - When the input has length n , the tape 2 head visits $O(S(n))$ cells

The complexity class L

- Exercise: $\text{PSPACE} = \bigcup_k \text{SPACE}(n^k)$
- **Definition:** $L = \text{SPACE}(\log n)$
- L is the set of languages that can be decided in **logarithmic space**




Example: Balanced binary strings

- $\text{BALANCED} = \{x \in \{0, 1\}^* : x \text{ has equal numbers of zeroes and ones}\}$
- **Claim:** $\text{BALANCED} \in \text{L}$
- **Proof sketch:** Given $x \in \{0, 1\}^n$:
 - Count the number of ones in x
 - Count the number of zeroes in x
 - Check whether the two counts are equal

} These counters are only $\log n$ bits each!

$$L \subseteq P$$

- Exercise: Show that $L \subseteq P$
- (Similar to the proof that $PSPACE \subseteq EXP$)



The L vs. P problem

- We expect that $L \neq P$, but we don't know how to prove it
- $L = P$ would mean that **every** efficient algorithm can be modified so that it only uses a **tiny** amount of work space

L vs. P vs. NP vs. PSPACE


- $L \subseteq P \subseteq NP \subseteq PSPACE$
- What we expect: All of these containments are strict
- What we can prove: At least one of these containments is strict:

Theorem: $L \neq PSPACE$

- (Proof omitted)

Nondeterministic log space computation

- **Definition:** **NL** is the class of languages that can be decided by a **nondeterministic** log-space Turing machine
- Equivalently, we imagine a log-space **verifier**
 - Technicality: Verifier reads certificate **one time** from left to right



The s - t connectivity problem

- $\text{STCONN} = \{\langle G, s, t \rangle : G \text{ is a digraph, } s \text{ and } t \text{ are vertices, and there is a directed path from } s \text{ to } t\}$
- **Claim:** $\text{STCONN} \in \text{NL}$
- **Proof sketch:** Take a **nondeterministic walk** through G starting from s for $|V|$ steps. If we ever reach t , accept; otherwise, reject.
- Verifier perspective: Certificate = path from s to t

Two surprises about NL

- We expect that $P \neq NP$. In contrast:

Savitch's Theorem: $NL \subseteq SPACE(\log^2 n)$

- We expect that $NP \neq coNP$. In contrast:

Immerman-Szelepcsényi Theorem: $NL = coNL$

Proof of Savitch's theorem

Savitch's Theorem: $NL \subseteq SPACE(\log^2 n)$

- Proof step 1: Show that $STCONN \in SPACE(\log^2 n)$
- Proof step 2: Show that $STCONN$ is “NL-complete”

Savitch's algorithm

- **Claim (Savitch's algorithm):** $\text{STCONN} \in \text{SPACE}(\log^2 n)$
- **Proof sketch:** Let's figure out: is there a path from s to t of length at most 2^k ?
 1. For all $m \in V$:
 - a) Recursively figure out whether there is a path from s to m of length at most 2^{k-1}
 - b) Recursively figure out whether there is a path from m to t of length at most 2^{k-1}
 - c) If both such paths exist, halt and accept
 2. Halt and reject
- Space complexity is $O(k \log n)$, which is $O(\log^2 n)$ when $k = \lceil \log |V| \rceil$

Proof of Savitch's theorem


Savitch's Theorem: $NL \subseteq SPACE(\log^2 n)$

- Proof step 1: Show that $STCONN \in SPACE(\log^2 n)$ ✓
- Proof step 2: Show that $STCONN$ is “NL-complete”

Log-space reductions

- To prove Savitch's theorem, we will use a **new type of reduction**
- Let $Y_1, Y_2 \subseteq \{0, 1\}^*$
- **Definition:** We write $Y_1 \leq_L Y_2$ if there exists $\Psi: \{0, 1\}^* \rightarrow \{0, 1\}^*$ such that
 - For every $w \in Y_1$, we have $\Psi(w) \in Y_2$ (“YES maps to YES”)
 - For every $w \notin Y_1$, we have $\Psi(w) \notin Y_2$ (“NO maps to NO”)
 - Ψ can be computed in $O(\log n)$ space ← Definition on next slides

Space-bounded “transducer”



Space complexity for string-valued functions

- Let $\Psi: \{0, 1\}^* \rightarrow \{0, 1\}^*$ and let $S: \mathbb{N} \rightarrow \mathbb{N}$
- **Def:** We say Ψ is **computable in $O(S)$ space** if there is a 3-tape TM M such that:
 - If we initialize M with w on tape 1, then it halts with $\Psi(w)$ on tape 3
 - M never modifies tape 1 and M 's behavior does not depend on what it reads on tape 3
 - The tape 1 head is always located within one cell of the input
 - When the input has length n , the tape 2 head visits $O(S(n))$ cells

NL-completeness

- Let $Y \subseteq \{0, 1\}^*$
- **Definition:** We say that Y is NL-complete if $Y \in \text{NL}$ and for every $Z \in \text{NL}$, we have $Z \leq_L Y$

STCONN is NL-complete

Theorem: STCONN is NL-complete

- **Proof:** We have already shown $\text{STCONN} \in \text{NL}$
- Now let M be a nondeterministic log-space TM that decides Y
- Reduction: $\Psi(w) = \langle G, s, t \rangle$
- Each vertex in G represents a “configuration” of M on w , namely, the internal state, the contents of the **work tape**, and the locations of heads

STCONN is NL-complete

- We put an edge from u to v if M can go from u to v in a single step (with w written on input tape)
- We let s = the initial configuration and t = the accepting configuration
- (Without loss of generality, the accepting configuration is unique)
- YES maps to YES ✓ NO maps to NO ✓
- Exercise: The reduction can be computed in $O(\log n)$ space ✓

Proof of Savitch's theorem

Savitch's Theorem: $NL \subseteq SPACE(\log^2 n)$

- Proof step 1: Show that $STCONN \in SPACE(\log^2 n)$ ✓
- Proof step 2: Show that $STCONN$ is NL -complete ✓
- Proof step 3: Show that $SPACE(\log^2 n)$ is **closed** under log-space mapping reductions